

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : 5% Carbon Dioxide // Nitrogen

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
Contact supplier for more information on uses.

Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification : Gasco
320 Scarlet Blvd, Oldsmar, Florida
34677, United States of America
www.gascogas.com

1.4. Emergency telephone number

Emergency telephone number : 1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage : P410+P403 - Protect from sunlight. Store in a well-ventilated place.

Labelling according to Directive 67/548/EEC or 1999/45/EC

No labelling applicable

2.3. Other hazards

: None.

SECTION 3: Composition/information on ingredients

3.1. Substances : Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|----------------|------------------------------------------------------------------------------|----|-----------------------------------------------------------------|
| Nitrogen | (CAS-No.) 7727-37-9 (EC-No.) 231-783-9 (EC Index-No.) (REACH-no) *1 | 95 | Press. Gas (Comp.), H280 |
| Carbon dioxide | (CAS-No.) 124-38-9 (EC-No.) 204-696-9 (EC Index-No.) (REACH-no) *1 | 5 | Press. Gas (Liq.), H280 |

Full text of R- and H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures**4.1. Description of first aid measures**

- Inhalation : Adverse effects not expected from this product.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

5.3. Advice for firefighters

- Specific methods
- : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
 - If possible, stop flow of product.
 - Use water spray or fog to knock down fire fumes if possible.
 - Move containers away from the fire area if this can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- : Act in accordance with local emergency plan.
- Stay upwind.

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

- : Ventilate area.

6.4. Reference to other sections

- : See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Safe use of the product
- : The product must be handled in accordance with good industrial hygiene and safety procedures.
 - Only experienced and properly instructed persons should handle gases under pressure.
 - Consider pressure relief device(s) in gas installations.
 - Ensure the complete gas system was (or is regularly) checked for leaks before use.
 - Do not smoke while handling product.
 - Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
 - Use only oxygen approved lubricants and oxygen approved sealings.
 - Avoid suck back of water, acid and alkalis.
 - Do not breathe gas.
 - Avoid release of product into atmosphere.



Safe handling of the gas receptacle : Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Carbon dioxide (124-38-9) | | |
|------------------------------------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OEL : Occupational Exposure Limits | | |
| EU | TWA IOELV (EU) 8 h [mg/m ³] | 9000 mg/m ³ |
| | TWA IOELV (EU) 8 h [ppm] | 5000 ppm |
| Austria | TWA (AT) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (AT) OEL 8h [ppm] | 5000 ppm |
| | STEL (AT) OEL 15min [mg/m ³] | 18000 mg/m ³ |
| | STEL (AT) OEL 15min [ppm] | 10000 ppm |
| Belgium | TWA (BE) OEL 8h [mg/m ³] | 9131 mg/m ³ |
| | TWA (BE) OEL 8h [ppm] | 5000 ppm |
| | STEL (BE) OEL 15min [mg/m ³] | 54784 mg/m ³ |
| | STEL (BE) OEL 15min [ppm] | 30000 ppm |
| | Remark (BE) | A: La mention A signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # De vermelding A |

| | | |
|----------------|-----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat. |
| Bulgaria | TWA (BG) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| Estonia | TWA (EE) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (EE) OEL 8h [ppm] | 5000 ppm |
| France | TWA (FR) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (FR) OEL 8h [ppm] | 5000 ppm |
| | Note (FR) | Valeurs réglementaires indicatives |
| Germany | Local name | Kohlenstoffdioxid |
| | TRGS 900 Occupational exposure limit value (mg/m ³) | 9100 mg/m ³ |
| | TRGS 900 Occupational exposure limit value (ppm) | 5000 ppm |
| | Remark (TRGS 900) | DFG,EU |
| Greece | TWA (GR) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (GR) OEL 8h [ppm] | 5000 ppm |
| | STEL (GR) OEL 15min [mg/m ³] | 54000 mg/m ³ |
| ACGIH | ACGIH TWA (ppm) | 5000 ppm |
| | ACGIH STEL (ppm) | 30000 ppm |
| | Remark (ACGIH) | Asphyxia |
| Italy | TWA (IT) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (IT) OEL 8h [ppm] | 5000 ppm |
| Latvia | TWA (LV) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (LV) OEL 8h [ppm] | 5000 ppm |
| Luxembourg | TWA (LU) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (LU) OEL 8h [ppm] | 5000 ppm |
| Slovenia | TWA (SL) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (SL) OEL 8h [ppm] | 5000 ppm |
| Spain | TWA (ES) OEL 8h [mg/m ³] | 9150 mg/m ³ |
| | TWA (ES) OEL 8h [ppm] | 5000 ppm |
| | NotesNotes | VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país). |
| Switzerland | TWA (CH) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (CH) OEL 8h [ppm] | 5000 ppm |
| | Remark (CH) | Asphyxie - NIOSH |
| Netherlands | MAC TWA 8H (NL) [mg/m ³] | 9000 mg/m ³ |
| United Kingdom | WEL - LTEL - UK [mg/m ³] | 9150 mg/m ³ |
| | WEL - LTEL - UK [ppm] | 5000 ppm |
| | WEL - STEL - UK [mg/m ³] | 27400 mg/m ³ |
| | WEL - STEL - UK [ppm] | 15000 ppm |
| Czech Republic | TWA (CZ) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (CZ) OEL 8h [ppm] | 5000 ppm |
| | STEL (CZ) OEL 15min [mg/m ³] | 45000 mg/m ³ |
| | STEL (CZ) OEL 15min [ppm] | 25020 ppm |
| Denmark | TWA (DK) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (DK) OEL 8h [ppm] | 5000 ppm |
| | Anmærkninger (DK) | E (betyder, at stoffet har en EF-grænseværdi) |
| Finland | TWA (FI) OEL 8h [mg/m ³] | 9100 mg/m ³ |
| | TWA (FI) OEL 8h [ppm] | 5000 ppm |
| Hungary | TWA (HU) OEL 8h [mg/m ³] | 9000 mg/m ³ |

| | Megjegyzések (HU) | EU2 |
|-----------|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ireland | OEL (IE)-(8-hour reference period) [mg/m ³] | 9000 mg/m ³ |
| | OEL (IE)-(8-hour reference period) [ppm] | 5000 ppm |
| | OEL (IE)-(15min reference period) [mg/m ³] | 27000 mg/m ³ |
| | OEL (IE)-(15min reference period) [ppm] | 15000 ppm |
| | Notes (IE) | IOELV |
| Lithuania | TWA (LT) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (LT) OEL 8h [ppm] | 5000 ppm |
| Malta | TWA (MT) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (MT) OEL 8h [ppm] | 5000 ppm |
| Norway | TWA (NO) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (NO) OEL 8h [ppm] | 5000 ppm |
| Poland | TWA (PL) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | STEL (PL) OEL 15min [mg/m ³] | 27000 mg/m ³ |
| Romania | TWA (RO) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (RO) OEL 8h [ppm] | 5000 ppm |
| Sweden | TWA (SV) OEL 8h [mg/m ³] | 9000 mg/m ³ |
| | TWA (SV) OEL 8h [ppm] | 5000 ppm |
| | STEL (SV) OEL 15min [mg/m ³] | 18000 mg/m ³ |
| | STEL (SV) OEL 15min [ppm] | 10000 ppm |
| | Anmärkning (SE) | V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas); 34 (Koldioxid används ofta som indikatorsubstans i arbetslokaler där luftföroreningar huvudsakligen uppkommer genom de personer som vistas där. Se särskilda regler om ventilation i föreskrifterna om arbetsplatsens utformning) |
| Portugal | TWA (PT) OEL 8h [ppm] | 5000 ppm |
| | STEL (PT) OEL 15min [ppm] | 30000 ppm |

DNEL (Derived-No Effect Level) : None established.

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

- : Systems under pressure should be regularly checked for leakages.
- Ensure exposure is below occupational exposure limits (where available).
- Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear safety glasses with side shields.
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection
 - Hand protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.
 - Other : Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and full face mask - EN 136.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

- : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas
- Colour : Mixture contains one or more component(s) which have the following colour(s):
Colourless.

Odour : Odourless.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH : Not applicable for gases and gas mixtures.

Melting point / Freezing point : Not applicable for gas mixtures.

Boiling point : Not applicable for gas mixtures.

Flash point : Not applicable for gases and gas mixtures.

Evaporation rate : Not applicable for gases and gas mixtures.

Flammability (solid, gas) : Non flammable.

Explosive limits : Non flammable.

Vapour density : Not applicable.

Relative density, gas (air=1) : Lighter or similar to air.

Partition coefficient n-octanol/water (Log Kow) : Not applicable for gas mixtures.

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

Viscosity : No reliable data available.

Explosive properties : Not applicable.

Oxidising properties : Not applicable.

9.2. Other information

Molar mass : Not applicable for gas mixtures.

Other data : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

- : No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

- : Stable under normal conditions.

10.3. Possibility of hazardous reactions

- : Heating may cause an explosion.

10.4. Conditions to avoid



: Avoid moisture in installation systems.

10.5. Incompatible materials

: For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

12.1. Toxicity

Assessment : Classification criteria are not met.

EC50 48h - Daphnia magna [mg/l] : No data available.

EC50 72h - Algae [mg/l] : No data available.

LC50 96 h - Fish [mg/l] : No data available.

Nitrogen (7727-37-9)

| | |
|---------------------------------|--------------------|
| EC50 48h - Daphnia magna [mg/l] | No data available. |
| EC50 72h - Algae [mg/l] | No data available. |
| LC50 96 h - Fish [mg/l] | No data available. |

Carbon dioxide (124-38-9)

| | |
|---------------------------------|--------------------|
| EC50 48h - Daphnia magna [mg/l] | No data available. |
| EC50 72h - Algae [mg/l] | No data available. |
| LC50 96 h - Fish [mg/l] | No data available. |

12.2. Persistence and degradability

Assessment : No data available.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects : No known effects from this product.

Effect on the ozone layer : None.

Effect on global warming : Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.

Do not discharge into any place where its accumulation could be dangerous.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.

Return unused product in original cylinder to supplier.

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number

UN-No. : 1950

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : AEROSOLS

Transport by air (ICAO-TI / IATA-DGR) : Aerosols, non-flammable

Transport by sea (IMDG) : AEROSOLS

14.3. Transport hazard class(es)

Labelling :



2.2 : Non-flammable, non-toxic gases.

Transport by road/rail (ADR/RID)

Class : 2

Classification code : 5A

Tunnel Restriction : E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2

Emergency Schedule (EmS) - Fire : F-D

Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable

Transport by air (ICAO-TI / IATA-DGR) : Not applicable

Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P207.
LP02

Transport by air (ICAO-TI / IATA-DGR)
Passenger and Cargo Aircraft : 203.



20DACO2N-5000MB

SDS Ref.:

Cargo Aircraft only : 203.
Transport by sea (IMDG) : P207.
LP200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.
Seveso Directive : 2012/18/EU (Seveso III) : Not covered.

National regulations

National legislation : Ensure all national/local regulations are observed.
Water hazard class (WGK) : nwg - Non-hazardous to water

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.

- Abbreviations and acronyms : ATE - Acute Toxicity Estimate
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
EINECS - European Inventory of Existing Commercial Chemical Substances
CAS# - Chemical Abstract Service number
PPE - Personal Protection Equipment
LC50 - Lethal Concentration to 50 % of a test population
RMM - Risk Management Measures
PBT - Persistent, Bioaccumulative and Toxic
vPvB - Very Persistent and Very Bioaccumulative
STOT- SE : Specific Target Organ Toxicity - Single Exposure
CSA - Chemical Safety Assessment
EN - European Standard
UN - United Nations
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA - International Air Transport Association
IMDG code - International Maritime Dangerous Goods
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
WGK - Water Hazard Class
STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
- Training advice : None.
- Further information : Classification using data from databases maintained by the European Industrial Gases Association (EIGA).
Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.

Full text of H- and EUH-statements

| | |
|--------------------|-----------------------------------------------------|
| Press. Gas (Comp.) | Gases under pressure : Compressed gas |
| Press. Gas (Liq.) | Gases under pressure : Liquefied gas |
| H280 | Contains gas under pressure; may explode if heated. |

- DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.